



ESP8266 AT Instruction Set

Version 0.23

Espressif Systems IOT Team

Copyright (c) 2015



Disclaimer and Copyright Notice

Information in this document, including URL references, is subject to change without notice.

THIS DOCUMENT IS PROVIDED AS IS WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY WARRANTY OF MERCHANTABILITY, NON-INFRINGEMENT, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY WARRANTY OTHERWISE ARISING OUT OF ANY PROPOSAL, SPECIFICATION OR SAMPLE. All liability, including liability for infringement of any proprietary rights, relating to use of information in this document is disclaimed. No licenses express or implied, by estoppel or otherwise, to any intellectual property rights are granted herein.

The WiFi Alliance Member Logo is a trademark of the WiFi Alliance.

All trade names, trademarks and registered trademarks mentioned in this document are property of their respective owners, and are hereby acknowledged.

Copyright © 2015 Espressif Systems Inc. All rights reserved.



Table of Contents

1. Preambles	6
2. Command DescriPtion	7
3. Basic AT Command Set	8
3.1. Overview	8
3.2. Commands	8
1. AT – Test AT startup	8
2. AT+RST – Restart module	9
3. AT+GMR – View version info	9
4. AT+GSLP – Enter deep-sleep mode	9
5. ATE – AT commands echo	9
6. AT+RESTORE – Factory reset	10
7. AT+UART – UART configuration	10
8. AT+UART_CUR – current UART configuration	12
9. AT+UART_DEF – default UART configuration	13
4. WiFi Functions Overview	14
4.1. Commands	16
1. AT+CWMODE – WiFi mode	16
2. AT+CWMODE_CUR – current WiFi mode	16
3. AT+CWMODE_DEF – default WiFi mode	18
4. AT+CWJAP – Connect to AP	19
5. AT+CWJAP_CUR – Connect to AP, for current	20
6. AT+CWJAP_DEF – Connect to AP, save as default	21
7. AT+CWLAP – List available APs	22
8. AT+CWQAP – Disconnect from AP	22
9. AT+CWSAP – Configuration of softAP mode	23
10. AT+CWSAP_CUR – Current config of softAP mode	24
11. AT+CWSAP_DEF – Default config of softAP mode	25
12. AT+CWLIF – IP of stations	25
13. AT+CWDHCP – Enable/Disable DHCP	26



14. AT+CWDHCP_CUR – Enable/Disable DHCP	27
15. AT+CWDHCP_DEF – Enable/Disable DHCP and save to Flash	28
16. AT+CWAUTOCONN – Auto connect to AP or not.....	28
17. AT+CIPSTAMAC – Set mac address of station	29
18. AT+CIPSTAMAC_CUR – Set mac address of station	29
19. AT+CIPSTAMAC_DEF – Set mac address of station, save as default	30
20. AT+CIPAPMAC – Set mac address of softAP	30
21. AT+CIPAPMAC_CUR – Set mac address of softAP	31
22. AT+CIPAPMAC_DEF – Set mac address of softAP and save as default ..	31
23. AT+CIPSTA – Set IP address of station	32
24. AT+CIPSTA_CUR – Set IP address of station	33
25. AT+CIPSTA_DEF – Set IP address of station and save as default	34
26. AT+ CIPAP – Set IP address of softAP	35
27. AT+CIPAP_CUR – Set IP address of softAP	36
28. AT+CIPAP_DEF – Set IP address of softAP, save as default	36
29. AT+CWSTARTSMART – Start SmartConfig	37
30. AT+CWSTOPSMART – stop SmartConfig	37
5. TCP/IP Related AT Commands	38
5.1. Overview	38
5.2. TCP/IP	39
1. AT+CIPSTATUS – Information about connection	39
2. AT+CIPSTART – Start connection.....	40
3. AT+CIPSEND – Send data	41
4. AT+CIPSENDEX – Send data	42
5. AT+CIPCLOSE – Close TCP or UDP connection.....	43
6. AT+CIFSR – Get local IP address	43
7. AT+CIPMUX – Enable multiple connections	44
8. AT+CIPSERVER – Configure as TCP server	44
9. AT+CIPMODE – Set transfer mode	45
10. AT+SAVETRANSLINK – Save transparent transmission link to Flash	45
11. AT+CIPSTO – Set TCP server timeout	47
12. AT+CIUPDATE – Update through network	47
13. AT+PING – Function Ping	48



14. +IPD – Receive network data	48
6. Appendix.....	49
7. Q&A.....	50




1. Preambles

This is the documentation for Espressif AT command Command set and usage.

Command set is divided into: Basic AT commands, WiFi function, AT commands, TCP / IP Toolbox AT commands.

Copy all files in folder "at" to folder "app" in `esp_iot_sdk` to compile.



Download:

`boot.bin`, downloads to flash `0x00000`

`user1.bin`, downloads to flash `0x01000`

`blank.bin`, factory initialize, downloads to flash both `0x7E000` and the last sector but one in flash, e.g. `0xFE000` for 1MB flash

Notes:

- Please make sure that correct BIN (`/esp_iot_sdk/bin/at`) is already in the chip (ESP8266) before the AT commands listed in this documentation can be used.
- AT added some functions so AT bin size is larger than before, please 1024KB(or larger) flash
- If you need to compile your own AT, please select 1024KB or larger option in STEP 5
- How to use 1024KB(or larger) flash, please refer to BBS <http://bbs.espressif.com/viewtopic.php?f=10&t=305>





2. Command DescriptiOn

Each Command set contains four types of AT commands.

Type	Command Format	DescriptiOn
Test	AT+<x>=?	Query the Set command or internal parameters and its range values.
Query	AT+<x>?	Returns the current value of the parameter.
Set	AT+<x>=<...>	Set the value of user-defined parameters in commands and run.
Execute	AT+<x>	Runs commands with no user-defined parameters.

Notes:

1. Not all AT Command has four commands.
2. [] = default value, not required or may not appear
3. String values require double quotation marks, for example:
`AT+CWSAP="ESP756290","21030826",1,4`
4. `Baudrate = 115200`
5. AT Commands has to be capitalized, and end with `"/r/n"`





3. Basic AT Command Set

3.1. Overview

The ESP8266 wireless WiFi modules can be driven via the serial interface using the standard AT commands. Here is a list of some basic AT commands that can be used.

Basic	
Command	Description
AT	Test AT startup
AT+RST	Restart module
AT+GMR	View version info
AT+GSLP	Enter deep-sleep mode
ATE	AT commands echo or not
AT+RESTORE	Factory Reset
AT+UART	UART configuration, [@deprecated]
AT+UART_CUR	UART current configuration
AT+UART_DEF	UART default configuration, save to flash

3.2. Commands

1. AT – Test AT startup

The type of this command is "executed". It's used to test the setup function of your wireless WiFi module.

AT - Test AT startup	
Response	OK
Parameters	null



2. AT+RST – Restart module

The type of this command is "executed". It's used to restart the module.

AT+RST - Restart module	
Response	OK
Parameters	null

3. AT+GMR – View version info

This AT command is used to check the version of AT commands and SDK that you are using, the type of which is "executed". The version information is made up of a string of numbers, the first four numbers refer to the version of AT commands, while the last four refer to the version of SDK.

AT+GMR - View version info	
Response	<number> OK
Parameters	< number > version info, length: 8 bytes
Notes	For example, response is 0017xxxx, then 0017 refer to the version of AT commands.

4. AT+GSLP – Enter deep-sleep mode

This command is used to invoke the deep-sleep mode of the module, the type of which is "set". A minor adjustment has to be made before the module enter this deep sleep mode, i.e., connect [XPD_DCDC](#) with [EXT_RSTB](#) via **OR**.

AT+GSLP=<time>	
Response	<time> OK
Parameters	The time unit of < time > is ms. ESP8266 will wake up after X ms and then enter the deep sleep mode.

5. ATE – AT commands echo

This command ATE is an AT trigger command echo. It means that entered commands can be echoed back to the sender when ATE command is used. Two parameters are possible. The command returns "OK" in normal cases and "ERROR" when a parameter other than 0 or 1 was specified.



ATE - AT commands echo	
Response	OK
Parameters	ATE0: Switch echo off ATE1: Switch echo on

6. AT+RESTORE – Factory reset

This command is used to restore the factory default settings of the module. The chip will be restarted when this command is executed.

AT+RESTORE - Factory reset	
Response	OK
Notes	Restore factory default settings. The chip will restart.

7. AT+UART – UART configuration

This command sets the UART configuration and writes the new configuration to the flash. It is stored as the default parameter and will also be used as the default baudrate henceforth. [THIS API IS DEPRECATED.]

AT+UART=<baudrate>,<databits>,<stopbits>,<parity>,<flow control> This API is deprecated, please use AT+UART_CUR or AT+UART_DEF instead.		
Example	AT+UART=115200,8,1,0,3	
Response	OK	
Parameters	<baudrate>	Baudrate range: 110 to 115200*40 (4.608 Mega)
	<databits>	5: 5 bits data 6: 6 bits data 7: 7 bits data 8: 8 bits data
	<stopbits>	1: 1 bit stop bit 2: 1.5 bit stop bit 3: 2 bit stop bit
	<parity>	0: None 1: Odd 2: EVEN
	<flow control>	0: disable flow control 1: enable RTS 2: enable CTS 3: enable both RTS and CTS



AT+UART=<baudrate>,<databits>,<stopbits>,<parity>,<flow control>

This API is deprecated, please use AT+UART_CUR or AT+UART_DEF instead.

Notes

- This configuration will also store the baud rate as the default rate in the user parameter area in the Flash for boot up.
- Flow control needs hardware support: MTCK is UART0 CTS and MTD0 is UART0 RTS.



8. AT+UART_CUR – current UART configuration

This command sets the current UART configuration; it does not write to the flash device. Hence there is no change in the default baudrate.

AT+UART_CUR=<baudrate>,<databits>,<stopbits>,<parity>,<flow control>		
Example	AT+UART_CUR=115200,8,1,0,3	
Response	OK	
Parameters	<baudrate>	Baudrate range: 110 to 115200*40 (4.608 Mega)
	<databits>	5: 5 bits data 6: 6 bits data 7: 7 bits data 8: 8 bits data
	<stopbits>	1: 1 bit stop bit 2: 1.5 bit stop bit 3: 2 bit stop bit
	<parity>	0: None 1: Odd 2: EVEN
	<flow control>	0: disable flow control 1: enable RTS 2: enable CTS 3: enable both RTS and CTS
Notes	<ul style="list-style-type: none">This configuration will NOT be stored in the flash; unlike the AT+UART command.Flow control needs hardware support: MTCK is UART0 CTS and MTDO is UART0 RTS.	



9. AT+UART_DEF – default UART configuration

This command sets the UART configuration and save it to flash. It is stored as the default parameter and will also be used as the default baudrate henceforth.

AT+UART_DEF=<baudrate>,<databits>,<stopbits>,<parity>,<flow control>		
Example	AT+UART_DEF=115200,8,1,0,3	
Response	OK	
Parameters	<baudrate>	Baudrate range: 110 to 115200*40 (4.608 Mega)
	<databits>	5: 5 bits data 6: 6 bits data 7: 7 bits data 8: 8 bits data
	<stopbits>	1: 1 bit stop bit 2: 1.5 bit stop bit 3: 2 bit stop bit
	<parity>	0: None 1: Odd 2: EVEN
	<flow control>	0: disable flow control 1: enable RTS 2: enable CTS 3: enable both RTS and CTS
Notes	<ul style="list-style-type: none">This configuration will be stored in the flash user parameter area.Flow control needs hardware support: MTCK is UART0 CTS and MTD0 is UART0 RTS.	



4. WiFi Functions Overview

WiFi Connectivity Functions Invoked by AT commands	
Command	Description
AT+CWMODE	WiFi mode (sta/AP/sta+AP) , [@deprecated]
AT+CWMODE_CUR	WiFi mode (sta/AP/sta+AP) Won't save to Flash
AT+CWMODE_DEF	WiFi default mode (sta/AP/sta+AP) Save to Flash
AT+CWJAP	Connect to AP, [@deprecated]
AT+CWJAP_CUR	Connect to AP, won't save to Flash
AT+CWJAP_DEF	Connect to AP, save to Flash
AT+CWLAP	Lists available APs
AT+CWQAP	Disconnect from AP
AT+CWSAP	Set configuration of ESP8266 softAP [@deprecated]
AT+CWSAP_CUR	Set configuration of ESP8266 softAP Won't save to Flash.
AT+CWSAP_DEF	Set configuration of ESP8266 softAP Save to Flash.
AT+CWLIF	Get station's IP which is connected to ESP8266 softAP
AT+CWDHCP	Enable/Disable DHCP, [@deprecated]
AT+CWDHCP_CUR	Enable/Disable DHCP, won't save to Flash
AT+CWDHCP_DEF	Enable/Disable DHCP, save to Flash
AT+CWAUTOCONN	Connect to AP automatically when power on
AT+CIPSTAMAC	Set mac address of ESP8266 station [@deprecated]
AT+CIPSTAMAC_CUR	Set mac address of ESP8266 station Won't save to Flash.



AT+CIPSTAMAC_DEF	Set mac address of ESP8266 station Save to Flash.
AT+CIPAPMAC	Set mac address of ESP8266 softAP [@deprecated]
AT+CIPAPMAC_CUR	Set mac address of ESP8266 softAP Won't save to Flash.
AT+CIPAPMAC_DEF	Set mac address of ESP8266 softAP Save to Flash.
AT+CIPSTA	Set IP address of ESP8266 station, [@deprecated]
AT+CIPSTA_CUR	Set IP address of ESP8266 station Won't save to Flash.
AT+CIPSTA_DEF	Set IP address of ESP8266 station Save to Flash.
AT+CIPAP	Set IP address of ESP8266 softAP, [@deprecated]
AT+CIPAP_CUR	Set IP address of ESP8266 softAP Won't save to Flash.
AT+CIPAP_DEF	Set IP address of ESP8266 softAP Save to Flash.



4.1. Commands

1. AT+CWMODE – WiFi mode

The function of this AT command is to get the value scope of WiFi mode, including station mode, softAP mode, and station+softAP mode, enquiry about the information of WiFi mode, or set the WiFi mode.

AT+CWMODE - WiFi mode	
[@deprecated]. Please use AT+CWMODE_CUR or AT+CWMODE_DEF instead.	
Command	AT+CWMODE=?
Response	+CWMODE:(value scope of <mode>) OK
Parameters	Please refer to AT command settings.
Command	AT+CWMODE?
Response	+CWMODE:<mode> OK
Parameters	Please refer to AT command settings.
Command	AT+CWMODE=<mode>
Response	OK
Parameters	<mode>1 means Station mode <mode>2 means softAP mode <mode>3 means AP + Station mode
Notes	This setting will be stored in the flash system parameter area. It won't be erased even when the power is off and restarted.

2. AT+CWMODE_CUR – current WiFi mode

There are three WiFi working modes: Station mode, softAP mode, and the co-existence of Station mode and softAP mode. This command is used to acquire the existing WiFi mode, or to set a customised WiFi mode.



AT+CWMODE_CUR - Set WIFI mode (sta/AP/sta+AP) , won't save to Flash	
Example	AT+CWMODE_CUR=3
Command	AT+CWMODE_CUR=?
Response	+CWMODE_CUR:(value scope of <mode>) OK
Parameters	<mode>1 means Station mode <mode>2 means softAP mode <mode>3 means AP + Station mode
Command	AT+CWMODE_CUR?
Response	+CWMODE_CUR:<mode> OK
Parameters	<mode>1 means Station mode <mode>2 means softAP mode <mode>3 means AP + Station mode
Command	AT+CWMODE_CUR=<mode>
Response	OK
Parameters	<mode>1 means Station mode <mode>2 means softAP mode <mode>3 means AP + Station mode
Notes	This configuration will not store in Flash.



3. AT+CWMODE_DEF – default WiFi mode

AT+CWMODE_DEF - WIFI mode (sta/AP/sta+AP), save to Flash	
Example	AT+CWMODE_DEF=3
Command	AT+CWMODE_DEF=?
Response	+CWMODE_DEF:(value scope of <mode>) OK
Parameters	<mode>1 means Station mode <mode>2 means softAP mode <mode>3 means AP + Station mode
Command	AT+CWMODE_DEF?
Response	+CWMODE_DEF:<mode> OK
Parameters	<mode>1 means Station mode <mode>2 means softAP mode <mode>3 means AP + Station mode
Command	AT+CWMODE_DEF=<mode>
Response	OK
Parameters	<mode>1 means Station mode <mode>2 means softAP mode <mode>3 means AP + Station mode
Notes	This configuration will store in Flash system parameter area.



4. AT+CWJAP – Connect to AP

AT+CWJAP - Connect to AP [<i>@deprecated</i>]. Please use AT+CWJAP_CUR or AT+CWJAP_DEF instead.	
Example	AT+ CWJAP ="abc", "0123456789" If SSID is "ab/,c" and password is "0123456789"/" AT+CWJAP ="ab///,c", "0123456789"/"//"
Command	AT+ CWJAP?
Response	+ CWJAP:<ssid> OK
Parameters	<ssid> string, AP's SSID
Command	AT+ CWJAP=<ssid>,< pwd >
Response	OK ERROR
Parameters	<ssid> string, AP's SSID <pwd> string, MAX: 64 bytes ASCII This command needs station mode enable. Escape character syntax is needed if "SSID" or "password" contains any special characters (' , ' \ ' ' ' and ' / ' ')
Notes	This configuration will store in Flash system parameter area.



5. AT+CWJAP_CUR – Connect to AP, for current

AT+CWJAP_CUR - Connect to AP, won't save to Flash	
Example	AT+CWJAP_CUR ="abc","0123456789" If SSID is "ab/,c" and password is "0123456789"/" AT+CWJAP_CUR="ab///,c","0123456789"/"/"
Command	AT+CWJAP_CUR?
Response	+CWJAP_CUR:<ssid> OK
Parameters	<ssid> string, AP's SSID
Command	AT+CWJAP_CUR=<ssid>,< pwd >
Response	OK ERROR
Parameters	<ssid> string, AP's SSID <pwd> string, MAX: 64 bytes ASCII This command needs station mode enable. Escape character syntax is needed if "SSID" or "password" contains any special characters (' , ' \ ' ' ' and ' / ' ')
Notes	This configuration will not store in Flash .



6. AT+CWJAP_DEF – Connect to AP, save as default

AT+CWJAP_DEF - Connect to AP and save AP info to flash	
Example	AT+CWJAP_DEF="abc","0123456789" If SSID is "ab/,c" and password is "0123456789"/" AT+CWJAP_DEF="ab///,c","0123456789"/"//"
Command	AT+CWJAP_DEF?
Response	+ CWJAP_DEF:<ssid> OK
Parameters	<ssid> string, AP's SSID
Command	AT+ CWJAP_DEF=<ssid>,< pwd >
Response	OK ERROR
Parameters	<ssid> string, AP's SSID <pwd> string, MAX: 64 bytes ASCII This command needs station mode enable. Escape character syntax is needed if "SSID" or "password" contains any special characters (',', '\', '\"' and '/')
Notes	This configuration will store in Flash system parameter area.



7. AT+CWLAP – List available APs

AT+CWLAP - Lists available APs	
Example	AT+CWLAP List of all available AP's detected by ESP8266 AT+CWLAP="wifi","ca:d7:19:d8:a6:44",6 Find AP with specific SSID and MAC at specific channel. AT+CWLAP="wifi" Find AP with specific SSID
Command	AT+CWLAP=<ssid>,<mac>,<ch>
Response	+CWLAP:<ecn>,<ssid>,<rssi>,<mac>,<ch> OK ERROR
Parameters	<ecn> 0 OPEN <ecn> 1 WEP <ecn> 2 WPA_PSK <ecn> 3 WPA2_PSK <ecn> 4 WPA_WPA2_PSK <ssid> string, SSID of AP <rssi> signal strength <mac> string, MAC address
Command	AT+CWLAP
Response	+CWLAP:<ecn>,<ssid>,<rssi>,<mac>,<ch> OK ERROR
Parameters	The same as above

8. AT+CWQAP – Disconnect from AP

AT+CWQAP - Disconnect from AP	
Command	AT+CWQAP=?
Response	OK
Parameters	null
Command	AT+ CWQAP
Response	OK
Parameters	null



9. AT+CWSAP – Configuration of softAP mode

AT+ CWSAP - Configuration of softAP mode [@deprecated]. Please use AT+CWSAP_CUR or AT+CWSAP_DEF instead.	
Example	AT+CWSAP="ESP8266","1234567890",5,3
Command	AT+ CWSAP?
Response	+ CWSAP:<ssid>,<pwd>,<chl>,<ecn>
Parameters	<code><ssid></code> string, ESP8266 softAP' SSID <code><pwd></code> string, MAX: 64 bytes ASCII <code><chl></code> channel id <code><ecn></code> 0 OPEN <code><ecn></code> 2 WPA_PSK <code><ecn></code> 3 WPA2_PSK <code><ecn></code> 4 WPA_WPA2_PSK
Command	AT+ CWSAP=<ssid>,<pwd>,<chl>,<ecn>
Response	OK ERROR
Parameters	The same as above.
Notes	This CMD is only available when softAP mode enable, and need to follow by AT+RST to make it works. ESP8266 softAP don't support WEP. This configuration will store in Flash system parameter area.

**10. AT+CWSAP_CUR – Current config of softAP mode**

AT+CWSAP_CUR - Set configuration of softAP mode, won't save to Flash	
Example	AT+CWSAP_CUR="ESP8266","1234567890",5,3
Command	AT+CWSAP_CUR?
Response	+CWSAP_CUR:<ssid>,<pwd>,<chl>,<ecn>
Parameters	<ssid> string, ESP8266 softAP' SSID <pwd> string, MAX: 64 bytes ASCII <chl> channel id <ecn> >0 OPEN <ecn> >2 WPA_PSK <ecn> >3 WPA2_PSK <ecn> >4 WPA_WPA2_PSK
Command	AT+CWSAP_CUR=<ssid>,<pwd>,<chl>,<ecn>
Response	OK ERROR
Parameters	The same as above.
Notes	This command is only available when softAP mode enable, and need to follow by AT+RST to make it works. ESP8266 softAP don't support WEP. This configuration will not store in Flash.

**11. AT+CWSAP_DEF – Default config of softAP mode**

AT+ CWSAP_DEF - Set configuration of softAP mode, save to Flash	
Example	AT+CWSAP_DEF="ESP8266","1234567890",5,3
Command	AT+ CWSAP_DEF?
Response	+ CWSAP_DEF:<ssid>,<pwd>,<chl>,<ecn>
Parameters	<ssid> string, ESP8266 softAP' SSID <pwd> string, MAX: 64 bytes ASCII <chl>channel id < ecn >0 OPEN < ecn >2 WPA_PSK < ecn >3 WPA2_PSK < ecn >4 WPA_WPA2_PSK
Command	AT+CWSAP_DEF=<ssid>,<pwd>,<chl>,<ecn>
Response	OK ERROR
Parameters	The same as above.
Notes	This command is only available when softAP mode enable, and need to follow by AT+RST to make it works. ESP8266 softAP don't support WEP. This configuration will store in Flash system parameter area.

12. AT+CWLIF – IP of stations

This command is used to get the IP of stations that are connected to ESP8266 softAP.

AT+ CWLIF- IP of stations which are connected to ESP8266 softAP	
Response	<IP addr>,<mac> OK
Parameters	<IP addr> IP address of stations which are connected to ESP8266 softAP <mac> mac address of stations which are connected to ESP8266 softAP

**13. AT+CWDHCP – Enable/Disable DHCP**

AT+ CWDHCP - Enable/Disable DHCP	
[@deprecated]. Please use AT+CWDHCP_CUR or AT+CWDHCP_DEF instead.	
Command	AT+CWDHCP?
Response	DHCP disabled or enabled now?
Parameters	Bit0: 0 - softap dhcp disable 1 - softap dhcp enable bit1: 0 - station dhcp disable 1 - station dhcp enable
Command	AT+CWDHCP=<mode>, <en>
Response	OK
Parameters	<mode> 0 : set ESP8266 softAP 1 : set ESP8266 station 2 : set both softAP and station <en> 0 : Disable DHCP 1 : Enable DHCP
Notes	This configuration will store in Flash user parameter area. This configuration interact with static IP related AT commands(AT+CIPSTA related and AT+CIPAP related): If enable DHCP, static IP will be disabled; If enable static IP, DHCP will be disabled; This will depends on the last configuration.

**14. AT+CWDHCP_CUR – Enable/Disable DHCP**

AT+CWDHCP_CUR - Enable/Disable DHCP, won't save to Flash	
Example	AT+CWDHCP_CUR=0,1
Command	AT+CWDHCP_CUR=<mode>, <en>
Response	OK
Parameters	<mode> 0 : set ESP8266 softAP 1 : set ESP8266 station 2 : set both softAP and station <en> 0 : Disable DHCP 1 : Enable DHCP
Notes	This configuration will not store in Flash. This configuration interact with static IP related AT commands(AT+CIPSTA related and AT+CIPAP related): If enable DHCP, static IP will be disabled; If enable static IP, DHCP will be disabled; This will depends on the last configuration.

**15. AT+CWDHCP_DEF – Enable/Disable DHCP and save to Flash**

AT+CWDHCP_DEF - Enable/Disable DHCP and save to Flash	
Example	AT+CWDHCP_CUR=0,1
Command	AT+CWDHCP_DEF=<mode>, <en>
Response	OK
Parameters	<mode> 0 : set ESP8266 softAP 1 : set ESP8266 station 2 : set both softAP and station <en> 0 : Disable DHCP 1 : Enable DHCP
Notes	This configuration will store in Flash user parameter area. This configuration interacts with static IP related AT commands(AT+CIPSTA related and AT+CIPAP related): If enable DHCP, static IP will be disabled; If enable static IP, DHCP will be disabled; This will depend on the last configuration.

16. AT+CWAUTOCONN – Auto connect to AP or not

AT+CWAUTOCONN - Connect to AP automatically or not	
Example	AT+CWAUTOCONN=1
Command	AT+CWAUTOCONN=<enable>
Response	OK
Parameters	<enable> 0 : do not auto-connect to AP when power on 1 : connect to AP automatically when power on Default is enable, ESP8266 station will connect to AP automatically when power on.
Notes	This configuration will store in Flash system parameter area.

**17. AT+CIPSTAMAC – Set mac address of station**

AT+ CIPSTAMAC - Set mac address of ESP8266 station [<i>@deprecated</i>]. Use AT+CIPSTAMAC_CUR or AT+CIPSTAMAC_DEF instead.	
Example	AT+CIPSTAMAC="18:fe:35:98:d3:7b"
Command	AT+CIPSTAMAC?
Response	+CIPSTAMAC:<mac> OK
Parameters	<mac> string, mac address of ESP8266 station
Command	AT+CIPSTAMAC=<mac>
Response	OK
Parameters	<mac> string, mac address of ESP8266 station
Notes	This configuration will store in Flash user parameter area.

18. AT+CIPSTAMAC_CUR – Set mac address of station

AT+ CIPSTAMAC_CUR - Set mac address of ESP8266 station, won't save to Flash	
Example	AT+CIPSTAMAC_CUR="18:fe:35:98:d3:7b"
Command	AT+CIPSTAMAC_CUR?
Response	+CIPSTAMAC_CUR:<mac> OK
Parameters	<mac> string, mac address of ESP8266 station
Command	AT+CIPSTAMAC_CUR=<mac>
Response	OK
Parameters	<mac> string, mac address of ESP8266 station
Notes	This configuration will not store in Flash.

**19. AT+CIPSTAMAC_DEF – Set mac address of station, save as default**

AT+ CIPSTAMAC_DEF - Set mac address of ESP8266 station, save to Flash	
Example	AT+CIPSTAMAC_DEF="18:fe:35:98:d3:7b"
Command	AT+CIPSTAMAC_DEF?
Response	+CIPSTAMAC_DEF:<mac> OK
Parameters	Param description <mac> string, mac address of ESP8266 station
Command	AT+CIPSTAMAC_DEF=<mac>
Response	OK
Parameters	<mac> string, mac address of ESP8266 station
Notes	This configuration will store in Flash user parameter area.

20. AT+CIPAPMAC – Set mac address of softAP

AT+ CIPAPMAC - Set mac address of ESP8266 softAP [@deprecated]. Use AT+CIPAPMAC_CUR or AT+CIPAPMAC_DEF instead.	
Example	AT+CIPAPMAC="1a:fe:36:97:d5:7b"
Command	AT+CIPAPMAC?
Response	+CIPAPMAC:<mac> OK
Parameters	<mac> string, mac address of ESP8266 softAP
Command	AT+CIPAPMAC=<mac>
Response	OK
Parameters	<mac> string, mac address of ESP8266 softAP
Notes	This configuration will store in Flash user parameter area.



21. AT+CIPAPMAC_CUR – Set mac address of softAP

AT+CIPAPMAC_CUR - Set mac addr of ESP8266 softAP, won't save to Flash	
Example	AT+CIPAPMAC_CUR="1a:fe:36:97:d5:7b"
Command	AT+CIPAPMAC_CUR?
Response	+CIPAPMAC_CUR:<mac> OK
Parameters	<mac> string, mac address of ESP8266 softAP
Command	AT+CIPAPMAC_CUR=<mac>
Response	OK
Parameters	<mac> string, mac address of ESP8266 softAP
Notes	This configuration will not store in Flash.

22. AT+CIPAPMAC_DEF – Set mac address of softAP and save as default

AT+ CIPAPMAC_DEF - Set mac address of ESP8266 softAP, save to Flash	
Example	AT+CIPAPMAC_DEF="1a:fe:36:97:d5:7b"
Command	AT+CIPAPMAC_DEF?
Response	+CIPAPMAC_DEF:<mac> OK
Parameters	<mac> string, mac address of ESP8266 softAP
Command	AT+CIPAPMAC_DEF=<mac>
Response	OK
Parameters	<mac> string, mac address of ESP8266 softAP
Notes	This configuration will store in Flash user parameter area.



23. AT+CIPSTA – Set IP address of station

AT+ CIPSTA - Set IP address of ESP8266 station [@deprecated]. Please use AT+CIPSTA_CUR or AT+CIPSTA_DEF instead.	
Example	AT+CIPSTA="192.168.6.100","192.168.6.1","255.255.255.0"
Command	AT+CIPSTA?
Response	+CIPSTA:<IP> OK
Parameters	<IP> string, IP address of ESP8266 station
Command	AT+CIPSTA=<IP>[,<gateway>,<netmask>]
Response	OK
Parameters	<IP> string, IP address of ESP8266 station [<gateway>] gateway [<netmask>] netmask
Notes	This configuration will store in Flash user parameter area. This configuration interacts with DHCP related AT commands(AT +CWDHCP related): If enable static IP, DHCP will be disabled; If enable DHCP, static IP will be disabled; This will depend on the last configuration.



24. AT+CIPSTA_CUR – Set IP address of station

AT+CIPSTA_CUR - Set IP address of ESP8266 station, won't save to Flash	
Example	AT+CIPSTA_CUR="192.168.6.100","192.168.6.1","255.255.255.0"
Command	AT+CIPSTA_CUR?
Response	+CIPSTA_CUR:<IP> OK
Parameters	Param description <IP> string, IP address of ESP8266 station
Command	AT+CIPSTA_CUR=<IP>[,<gateway>,<netmask>]
Response	OK
Parameters	<IP> string, IP address of ESP8266 station [<gateway>] gateway [<netmask>] netmask
Notes	This configuration will not store in Flash. This configuration interacts with DHCP related AT commands(AT +CWDHCP related): If enable static IP, DHCP will be disabled; If enable DHCP, static IP will be disabled; This will depend on the last configuration.

**25. AT+CIPSTA_DEF – Set IP address of station and save as default**

AT+CIPSTA_DEF - Set IP address of ESP8266 station, save to Flash	
Example	AT+CIPSTA_DEF="192.168.6.100","192.168.6.1","255.255.255.0"
Command	AT+CIPSTA_DEF?
Response	+CIPSTA:<IP> OK
Parameters	<IP> string, IP address of ESP8266 station
Command	AT+CIPSTA_DEF=<IP>[,<gateway>,<netmask>]
Response	OK
Parameters	<IP> string, IP address of ESP8266 station [<gateway>] gateway [<netmask>] netmask
Notes	This configuration will store in Flash user parameter area. This configuration interacts with DHCP related AT commands(AT +CWDHCP related): If enable static IP, DHCP will be disabled; If enable DHCP, static IP will be disabled; This will depend on the last configuration.

**26. AT+ CIPAP – Set IP address of softAP**

AT+ CIPAP - Set IP address of ESP8266 softAP [@deprecated]. Please use AT+CIPAP_CUR or AT+CIPAP_DEF instead.	
Example	AT+CIPAP="192.168.5.1"
Command	AT+CIPAP?
Response	+CIPAP:<IP> OK
Parameters	<IP> string, IP address of ESP8266 softAP
Command	AT+CIPAP=<IP>
Response	OK
Parameters	<IP> string, IP address of ESP8266 softAP
Notes	This configuration will store in Flash user parameter area. This configuration interacts with DHCP related AT commands(AT +CWDHCP related): If enable static IP, DHCP will be disabled; If enable DHCP, static IP will be disabled; This will depend on the last configuration.

**27. AT+CIPAP_CUR – Set IP address of softAP**

AT+CIPAP_CUR - Set IP address of ESP8266 softAP, won't save to Flash	
Example	AT+CIPAP_CUR="192.168.5.1"
Command	AT+CIPAP_CUR?
Response	+CIPAP_CUR:<IP> OK
Parameters	<IP> string, IP address of ESP8266 softAP
Command	AT+CIPAP_CUR=<IP>
Response	OK
Parameters	<IP> string, IP address of ESP8266 softAP
Notes	This configuration will not store in Flash. This configuration interacts with DHCP related AT commands(AT +CWDHCP related): If enable static IP, DHCP will be disabled; If enable DHCP, static IP will be disabled; This will depend on the last configuration.

28. AT+CIPAP_DEF – Set IP address of softAP, save as default

AT+ CIPAP_DEF - Set IP address of ESP8266 softAP, save to Flash	
Example	AT+CIPAP_DEF="192.168.5.1"
Command	AT+CIPAP_DEF?
Response	+CIPAP_DEF:<IP> OK
Parameters	<IP> string, IP address of ESP8266 softAP
Command	AT+CIPAP_DEF=<IP>
Response	OK
Parameters	<IP> string, IP address of ESP8266 softAP
Notes	This configuration will store in Flash user parameter area. This configuration interacts with DHCP related AT commands(AT +CWDHCP related): If enable static IP, DHCP will be disabled; If enable DHCP, static IP will be disabled; This will depend on the last configuration.



29. AT+CWSTARTSMART – Start SmartConfig

AT+CWSTARTSMART - Start SmartConfig	
Example	AT+CWMODE=1 AT+CWSTARTSMART=1
Command	AT+CWSTARTSMART =<type>
Response	OK
Parameters	< type> SmartConfig protocol type 1: ESP_TOUCH 2: AirKiss
Notes	<ul style="list-style-type: none">• You can apply for more documents about our SmartConfig from Espressif.• ESP8266 station has to be enable• Message "Smart get wifi info" means Smart Config succeed, then you can use "AT+CIFSR" to check whether it got IP from router or not.• ESP8266 can't do anything during SmartConfig so please wait till it succeed or use command "AT+CWSTOPSMART" to stop SmartConfig.

30. AT+CWSTOPSMART – stop SmartConfig

AT+CWSTOPSMART stop SmartConfig	
Command	AT+CWSTOPSMART
Response	OK
Notes	No matter SmartConfig succeed or not, please always call "AT+CWSTOPSMART" to release the buffer it took.



5. TCP/IP Related AT Commands

5.1. Overview

TCP/IP	
Command	Description
AT+ CIPSTATUS	Get connection status
AT+CIPSTART	Establish TCP connection or register UDP port
AT+CIPSEND	Send data
AT+CIPCLOSE	Close TCP/UDP connection
AT+CIFSR	Get local IP address
AT+CIPMUX	Set multiple connections mode
AT+CIPSERVER	Configure as server
AT+CIPMODE	Set transmission mode
AT+SAVETRANSLINK	Save transparent transmission link to Flash
AT+CIPSTO	Set timeout when ESP8266 runs as TCP server
AT+CIUPDATE	Upgrade firmware through network
AT+PING	Function PING



5.2. TCP/IP

1. AT+CIPSTATUS – Information about connection

AT+CIPSTATUS – Information about connection	
Command	AT+CIPSTATUS
Response	STATUS:<stat> +CIPSTATUS:<ID>,<type>,<remote_IP>,<remote_port> ,<local_port>,<te type>
Parameters	<stat> <stat> 2: Got IP <stat> 3: Connected <stat> 4: Disconnected <id> id of the connection (0~4), for multi-connect <type> string, "TCP" or "UDP" <remote_IP> string, remote IP address. <remote_port> remote port number <local_port> ESP8266 local port number <tetype> <tetype> 0: ESP8266 runs as client <tetype> 1: ESP8266 runs as server

**2. AT+CIPSTART – Start connection**

AT+CIPSTART - Establish TCP connection or register UDP port, start connection	
Example	AT+CIPSTART="TCP","192.168.101.110",1000 Refer to "Espressif AT Command Examples"
Command	AT+CIPSTART=?
Response	1) If AT+CIPMUX=0 +CIPSTART:(<type>),(<IP address>),(<port>)[,(<local port>),(<mode>)] +CIPSTART:(<type>),(<domain name>),(<port>)[,(<local port>),(<mode>)] OK 2) If AT+CIPMUX=1 +CIPSTART:(id),(<type>),(<IP address>),(<port>)[,(<local port>),(<mode>)] +CIPSTART: (id), (<type>),(<domain name>),(<port>)[,(<local port>),(<mode>)]
Parameters	null
Single connection	(+CIPMUX=0) AT+CIPSTART=<type>,<addr>,<port>[,<UDP local port>,<UDP mode>] [,<TCP keep alive>]
Multiple connection	(+CIPMUX=1) AT+CIPSTART=<id>,<type>,<addr>,<port>[,<UDP local port>,<UDP mode>][,<TCP keep alive>]
Response	OK or ERROR If connection already exists, returns ALREAY CONNECT
Parameters	<id> 0-4 , id of connection <type> string, "TCP" or "UDP" <addr> string, remote IP <port> string, remote port [<UDP local port>] for UDP only [<UDP mode>] In UDP transparent transmission, it has to be 0. [<UDP mode>] 0 : destination peer entity of UDP will not change. [<UDP mode>] 1 : destination peer entity of UDP can change once. [<UDP mode>] 2 : destination peer entity of UDP is allowed to change. Note: [<UDP mode>] can only be used when [<UDP local port>] is set. [<TCP keep alive>] default 0. unit: 500 milliseconds. [<TCP keep alive>] 0 : disable TCP keep-alive [<TCP keep alive>] 1 ~ 7200 : TCP keep-alive interval



3. AT+CIPSEND – Send data

AT+CIPSEND - Send data	
Command	AT+CIPSEND=?
Response	OK
Parameters	null
Single connection	(+CIPMUX=0) AT+CIPSEND=<length>
Multiple connection	(+CIPMUX=1) AT+CIPSEND=<id>,<length>
UDP Transmission	AT+CIPSEND=[<id>,<length>[,<remote IP>,<remote port>]
Response	Wrap return ">" after set command. Begins receive of serial data, when data length is met, starts transmission of data. If connection cannot be established or gets disconnected during send, returns ERROR If data is transmitted successfully, returns SEND OK
Parameters	<id> ID no. of transmit connection <length> data length, MAX 2048 bytes
Command	AT+CIPSEND
Response	Wrap return ">" after execute command. Enters unvarnished transmission, 20ms interval between each packet, maximum 2048 bytes per packet. When single packet containing "+++" is received, it returns to normal command mode. This command can only be used in transparent transmission mode which require to be single connection mode. For UDP transparent transmission, <UDP mode> has to be 0 in command "AT+CIPSTART"
Notes	Please refer to "Espressif AT Command Examples" for more examples.



4. AT+CIPSENDEX – Send data

AT+CIPSENDEX - Send data	
Command	AT+CIPSENDEX=?
Response	OK
Parameters	null
Single connection	(+CIPMUX=0) AT+CIPSENDEX=<length>
Multiple connection	(+CIPMUX=1) AT+CIPSENDEX=<id>,<length>
UDP Transmission	AT+CIPSENDEX=[<id>,<length>[,<remote IP>,<remote port>]
Response	Wrap return ">" after set command. Begins receive of serial data, when data length or "\0" is met, starts transmission of data. So if sending "\0" is needed, please send it as "\\0" If connection cannot be established or gets disconnected during send, returns ERROR If data is transmitted successfully, returns SEND OK
Parameters	<id> ID no. of transmit connection <length> data length, MAX 2048 bytes

**5. AT+CIPCLOSE – Close TCP or UDP connection**

AT+CIPCLOSE - Close TCP or UDP connection	
Command	AT+CIPCLOSE=?
Response	OK
Multiple connection	AT+CIPCLOSE=<id>
Response	No errors, returns OK If connection <id> is disconnected, returns Link is not
Parameters	<id> ID no. of connection to close, when id=5, all connections will be closed. (id=5 has no effect in server mode)
Single connection	AT+CIPCLOSE
Response	OK or If no such connection, returns ERROR Prints UNLINK when there is no connection

6. AT+CIFSR – Get local IP address

AT+CIFSR - Get local IP address	
Command	AT+CIFSR=?
Response	OK
Command	AT+ CIFSR
Response	+ CIFSR:<IP address> + CIFSR:<IP address> OK ERROR
Parameters	<IP address> IP address of ESP8266 softAP IP address of ESP8266 station



7. AT+CIPMUX – Enable multiple connections

AT+ CIPMUX - Enable multiple connections or not	
Example	AT+CIPMUX=1
Command	AT+CIPMUX?
Response	+ CIPMUX:<mode> OK
Parameters	<mode>0 single connection <mode>1 multiple connection
Command	AT+CIPMUX=<mode>
Response	OK If already connected, returns Link is builded
Parameters	The same as above.
Notes	1. "AT+CIPMUX=1" can only be set when transparent transmission disabled ("AT+CIPMODE=0") 2. This mode can only be changed after all connections are disconnected. If server is started, reboot is required.

8. AT+CIPSERVER – Configure as TCP server

AT+ CIPSERVER - Configure as TCP server	
Example	AT+ CIPMUX=1 AT+ CIPSERVER=1,1001
Command	AT+ CIPSERVER=<mode>[,<port>]
Response	OK
Parameters	<mode>0 Delete server (need to follow by restart) <mode>1 Create server <port> port number, default is 333
Notes	1. Server can only be created when AT+CIPMUX=1 2. Server monitor will automatically be created when Server is created. 3. When a client is connected to the server, it will take up one connection, be gave an id.



9. AT+CIPMODE – Set transfer mode

AT+ CIPMODE - Set transfer mode	
Example	AT+CIPMODE=1
Command	AT+ CIPMODE?
Response	+ CIPMODE:<mode> OK
Parameters	<mode>0 normal mode <mode>1 unvarnished transmission mode, only for TCP single connection.
Command	AT+CIPMODE=<mode>
Response	OK If already connected, returns Link is builded
Parameters	<mode>0 normal mode <mode>1 unvarnished transmission mode, only for TCP single connection.
Notes	This configuration would not save into Flash.

10. AT+SAVETRANSLINK – Save transparent transmission link to Flash

AT+SAVETRANSLINK - Save transparent transmission link to Flash	
Example	AT+SAVETRANSLINK=1,"192.168.6.110",1002,"TCP"
Command	AT+SAVETRANSLINK =<mode>,<IP>,<port>[,<type>]
Response	OK or ERROR
Parameters	<mode>0 normal mode <mode>1 transparent transmission mode <IP> remote IP <port> remote port [<type>] TCP or UDP, default to be "TCP"
Notes	1. This command will save the transparent transmission mode and its TCP link into Flash user parameter area. 2. As long as the IP, port numerical conformance to specification, we will save them to Flash





11. AT+CIPSTO – Set TCP server timeout

AT+ CIPSTO - Set TCP server timeout	
Example	AT+ CIPMUX=1 AT+ CIPSERVER=1,1001 AT+CIPSTO=10
Command	AT+CIPSTO?
Response	+ CIPSTO:<time> OK
Parameters	Param description The same as below.
Command	AT+CIPSTO=<time>
Response	OK
Parameters	Param description < time> TCP server timeout, range 0~7200 seconds
Notes	ESP8266 as TCP server, will disconnect to TCP client that didn't communicate with it even if timeout. If AT+CIPSTO=0, it will never timeout. We don't recommend that.

12. AT+CIUPDATE – Update through network

AT+ CIUPDATE - update through network	
Command	AT+ CIUPDATE
Response	+CIPUPDATE:<n> OK
Parameters	<n> 1 found server <n> 2 connect server <n> 3 got edition <n> 4 start update
Notes	Firmware upgrade depends on network condition. It will return ERROR if upgrade fail, please wait a while. 1. If using Espressif AT BIN (\esp_iot_sdk\bin\at), "AT+CIUPDATE" will download new AT BIN from Espressif Cloud. 2. If using user-compiled AT BIN, users need to make their own "AT+CIUPDATE" to upgrade, Espressif provide a demo in \esp_iot_sdk\example\at 3. AT BINs on server have to be named as "user1.bin" and "user2.bin"



13. AT+PING – Function Ping

AT+PING - Function Ping	
Example	AT+PING="192.168.1.1" AT+PING="www.baidu.com"
Command	AT+PING=<IP>
Response	+<time> OK Or ERROR // means ping fail
Parameters	Param description <IP> : string, host IP or domain name <time> : response time of ping

14. +IPD – Receive network data

+IPD - Receive network data	
Single connection	(+CIPMUX=0) +IPD,<len>:<data>
Multiple connection	(+CIPMUX=1) +IPD,<id>,<len>:<data>
Parameters	<id> id no. of connection <len> data length <data> data received
Notes	When the module receives network data, it will send the data through the serial port using +IPD command.



6. Appendix

ESP8266 AT commands below will save configuration into Flash:

Command	Example
Save in Flash user parameter area	
AT+UART_DEF	AT+UART_DEF=115200,8,1,0,3
AT+CWDHCP_DEF	AT+CWDHCP_DEF=1,1
AT+CIPSTAMAC_DEF	AT+CIPSTAMAC_DEF="18:fe:35:98:d3:7b"
AT+CIPAPMAC_DEF	AT+CIPAPMAC_DEF="1a:fe:36:97:d5:7b"
AT+CIPSTA_DEF	AT+CIPSTA_DEF="192.168.6.100"
AT+CIPAP_DEF	AT+CIPAP_DEF="192.168.5.1"
AT+SAVETRANSLINK	AT+SAVETRANSLINK=1,"192.168.6.10",1001
Save in Flash system parameter area	
AT+CWMODE_DEF	AT+CWMODE_DEF=3
AT+CWJAP_DEF	AT+CWJAP_DEF="abc", "0123456789"
AT+CWSAP_DEF	AT+CWSAP_DEF="ESP8266","12345678",5,3
AT+CWAUTOCONN	AT+CWAUTOCONN=1

Notes:

- We will check the new setting with original configuration from flash first, only if the configuration changes, we will write it to flash.
- To 512KB flash, default setting:
 - user parameter area is 0x3C000 ~ 0x40000, 16KB;
 - system parameter area is 0x7C000~0x80000, 16KB
- To 1MB flash (or larger than 1MB), default setting:
 - user parameter area is 0x7C000 ~ 0x80000, 16KB;
 - system parameter area is the last 16KB of flash.



7. Q&A

If you have any questions about AT Commands, please contact us (support-at@espressif.com) with information as follows:

- **Version info of AT** : Using "AT+GMR" to get the version info.
Hardware Module info: example Ai-thnker ESP-01
- **Screenshot or steps of the test steps**, for example:



- **Log:**
ets Jan 8 2013,rst cause: 1, boot mode: (3,3)

```
load 0x40100000, len 26336, room 16
tail 0
chksum 0xde
load 0x3ffe8000, len 5672, room 8
tail 0
chksum 0x69
load 0x3ffe9630, len 8348, room 8
tail 4
chksum 0xcb
csum 0xcb
SDK version: 0.9.1
addr not ack when tx write cmd
mode : sta(18: fe: 34: 97: d5: 7b) + softAP(1a: fe: 34: 97: d5: 7b)
```